

PNEUMATIC LOADING/UNLOADING CLAMP TO PICK UP AND TRANSPORT TUBES OR HEATING ELEMENTS

This is a pneumatic clamp specially designed to simultaneously pick up tubes from the presetter or the heating elements from the filling machine, to facilitate their transportation to the next machine and so operation.

Because of the weight of the clamp in addition to the tubes/heating elements being carried, it is recommended that a suitable counterweight is used.

Tube diameter (to be defined): 7.5-10 mm.

AVAILABLE VERSION

PNEUMATIC VERSION


Pneumatic clamp to pick up and transport tubes.

Weight: 8 Kg. Minimum tube length: 300 mm


MECHANIC VERSION

Mechanic clamp to pick up and transport tubes.

Weight: 3 Kg. Tube length: 240-500 mm



Mod. 135/31.000000 30-tube version **Mod. 134/31.000000** 24-tube version



Mod. 135/32.000000 30-tube version

Mod. 134/32.00000 24-tube version

OPTIONS

Mod. 135/31.100000 Adjustable counter-weight, min. 8 Kg, to support the weight of the

clamp with either empty or filled tubes so as to relieve the operator from this burden and to enable the easy loading of the empty tubes

and unloading of the filled tubes.

Mod. 135/31.000050 Set of parts subject to wear